

Product Information (Internal Use Only)
Not for External Distribution



SKU 960-001217
Marketing Name RALLY
Placement B2B and Amazon US/CAN only
Embargo Date: 06-Jun-2018

Product Line	Bolide	Product Life Cycle Status:	Pre-Release
US MSRP	1,999.99	OSD Date	01-Nov-2018
US STP*	1,849.99	XDC Launch Date	01-Oct-2018
CND MSRP	2,599.99	LPA Date	-
CND STP*	2,404.99		
MXN MSRP	43,999.00		
Last Update Date	11-Jul-2018	Warranty	2-year Limited hardware warranty

**Disclaimer: Disti pricing is the same as STP only when pricing is opened up to Disti. Exception: Disti pricing will vary from STP when sku is only opened up for Limited Channel Placement. Please refer to channel placement details.*

Product Description

Category	Pre-Release
SubCategory	-
Product Family	Pre-Release
Product/Service Category	Pre-Release
Product Heading/Tagline (ie. 25-Word Description)	Logitech Rally sets a new standard for USB-connected conference camera systems, uniting premium design and materials with unmatched audio and video performance.
Feature Benefits	Studio-quality video with Ultra-HD clarity Modular audio supports up to 2 speakers and 7 mic pods Premium design and materials complement any room RightSense™ technologies and design innovations automate a better user experience Table and Display Hubs minimize cross-room cabling
Package Contents	<p>Logitech Rally</p> <ul style="list-style-type: none"> Rally Camera Rally Display Hub Rally Table Hub Rally Speaker (x1) Rally Mic Pod (x1) Remote control USB Type C to USB Type C USB Type A to USB Type B CAT6A Ethernet cable HDMI Type A (x2) A/C cables (x2) Power Supplies (x2) Documentation <p>Logitech Rally Plus</p> <p>As above, except:</p> <ul style="list-style-type: none"> Rally Speaker (x2) Rally Mic Pod (x2)
Technical Specifications	<p>RALLY CAMERA</p> <p>Ultra-HD imaging system supports: 4K, 1440p, 1080p, 900p, 720p, and SD at 30 fps 1080p, 720p at 30 fps and 60 fps Smooth motorized pan, tilt and zoom Pan: ±90° Tilt: +50° / -90° 15x HD zoom 90° field of view Adaptive pan and tilt speed up to 70°/second (slows when zoomed in for easier control) Automatic inversion detection to correct image orientation and camera controls when mounted upside down Autofocus 3 camera presets Kensington security slot Video mute/unmute LED indicator Standard tripod thread Lens parks at -90° in sleep mode for assured privacy</p> <p>RALLY MIC POD</p> <p>Pickup range: 15 ft / 4.5m diameter Four omnidirectional microphones forming eight acoustic beams AEC (Acoustic Echo Cancellation)</p>

VAD (Voice Activity Detector)
Background noise suppression
Mute button with LED status indicator
Captive 9.6 ft (2.95m) 12-pin cable
Daisy chain up to 7 Rally Mic Pods
Frequency response: 90Hz – 16kHz
Sensitivity: >-27dB +/-1dB @ 1Pa
Microphone data rate: 48 kHz

Recommended # of participants:
Rally (one Mic Pod): 10
Rally Plus (two Mic Pods): 16
Additional participants per Mic Pod: 6
Recommended participants for Rally with 7 Mic Pods: 46

RALLY SPEAKER

High-performance 3" (76mm) driver with rare-earth magnet
Patent-pending suspension system eliminates vibration-induced camera shake and audio interference
Mini XLR cable connects to Rally Display Hub for both signal and power
Speaker volume 95dB SPL @1W, 100dB SPL @7.5W, both +/-2dB at ½ meter
Sensitivity: 95+/-2dB SPL at ½ meter
Distortion: 200Hz–300Hz < 2.5%, 300Hz–10kHz < 1%@7.5W
Speaker sampling rate: 48 kHz

RALLY TABLE HUB

Single CAT6A cable connection to Rally Display Hub (16.4 ft / 5m cable included, supports customer-supplied cables up to 164 ft (50 m)
Active speaker detection: analyzes audio from up to 7 Mic Pods and 56 beams every 8ms
12 Pin connector for Rally Mic Pod
HDMI Type A passthrough to Display Hub (x2)
USB Type C
USB Type A (reserved for future capability)
USB Type B (connects to meeting room computer)
RJ45 (reserved for future capability)
Power input

RALLY DISPLAY HUB

HDMI Type A (x2) (connects to displays)
USB C (connects to Rally Camera)
USB Type B (connects to meeting room computer)
RJ45 (connects to Table Hub)
Mini XLR (x2)
Powers one or two Rally Speakers
Power input

REMOTE CONTROL

RF remote control (line of sight not required)
CR2032 batteries (included)

CABLES / POWER

Camera to Display Hub
6.5 ft (2m) USB 3.1 Type C to USB Type C 3.1

Conference Room Computer to Display or Table Hub
6.5 ft (2m) USB 3.1 Type A to USB Type B

Display Hub to Table Hub
16.4 ft (5m) CAT6A Ethernet cable (supports customer-supplied cables up to 164 ft (50 m)

Display Hub to Speaker (x2)
9.6 ft (2.95m) Mini XLR (supports customer-supplied extension cables up to 9.8 ft (3m)

Conference Room Computer to Displays (x2)
6.5 ft (2m) HDMI A

Mic Pod
9.6 ft (2.95m): Hardwired with 12 pin connector

Power Outlets to Power Supplies (x2)
3.2 ft (1m)

Power Supplies to Table Hub / Display Hub (x2)
4.9 ft (1.5m)

AVAILABLE ACCESSORIES

RALLY MOUNTING KIT

Rally Mounting Kit with cable retainers (x2) and mounting brackets for camera, speakers (x2), and hubs (x2)

RALLY MIC POD

Deploy up to 7 Rally Mic Pods for greater audio coverage in larger rooms

RALLY MIC POD HUB

Connect 1-3 Rally Mic Pods (or additional hubs) for placement flexibility and under-table cabling

Product Set-Up Information

Pallet Quantity - PLT Quantity 20
Units GMA

Country of Origin	CN	Primary Pack UPC	097855140203
Intermediate Pack Count	0	Intermediate Pack UPC	
Outer Case Pack Count	1	Master Shipper Carton UPC	00097855140203
URL Link to Datasheets	-		

	Weight (oz)	Length (in)	Width (in)	Height/Depth (in)
Primary Pack	300.71	27.56	10.83	8.66
Intermediate Pack	0.00	0.00	0.00	0.00
Master Shipper Carton	335.10	28.43	11.54	9.25